# This Page Is Inserted by IFW Operations and is not a part of the Official Record

# BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

# IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

## WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



#### INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:

C08F 8/40, C09D 5/38, C09C 1/64

(11) International Publication Number:

WO 99/06450

A1 (43) International Publication Date:

11 February 1999 (11.02.99)

(21) International Application Number:

PCT/US98/15761

(22) International Filing Date:

29 July 1998 (29.07.98)

GB, GR, IE, IT, LU, MC, NL, PT, SE).

(81) Designated States: AU, BR, CA, IL, JP, KR, MX, NZ, US,

European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,

(30) Priority Data:

60/054.179

30 July 1997 (30.07.97)

US

**Published** 

With international search report.

(71) Applicant (for all designated States except US): E.I. DU PONT DE NEMOURS AND COMPANY [US/US]; 1007 Market Street, Wilmington, DE 19898 (US).


(72) Inventors; and

- (75) Inventors/Applicants (for US only): BRUYLANTS, Paul, Peter [BE/BE]; Vinkenlaan 11, B-3191 Boortmeerbeek (BE). HUYBRECHTS, Josef [BE/BE]; Korenbloemstraat 39, B-2360 Oud-Turnhout (BE). KIRSHENBAUM, Kenneth, S. [US/US]; 4160 Wendell Road, West Bloomfield, MI 48323 (US). BERGE, Charles, T. [US/US]; 2948 Mohawk Lane, Rochester Hills, MI 48306 (US).
- (74) Agent: COSTELLO, James, A.; E.I. du Pont de Nemours and Company, Legal Patent Records Center, 1007 Market Street, Wilmington, DE 19898 (US).

(54) Title: PHOSPHONIC ACID REACTION PRODUCTS AND USE IN COATING COMPOSITIONS

(57) Abstract

The invention provides an aqueous coating composition comprising nonionically and/or anionically stabilized film-forming polymers and metallic pigments and a compound which is the reaction product of a



(1)

( || )

phosphonic acid derivative, a hydroxy-functional addition polymers and, optionally a compound having a hydroxy group, in which the phosphonic acid derivative is selected from one or both of (I) and (II), wherein R and R' are selected from the group consisting of an aliphatic and an aromatic substituent having 1 to 25 carbon atoms optionally including heteroatoms of at least one of oxygen, phosphorus and silicon.

## FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
ΑT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
ΑZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	ſΕ	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	ΙT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand	2.,	Zimbaowe
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	. Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

5

\$

#### TITLE

# PHOSPHONIC ACID REACTION PRODUCTS AND USE IN COATING COMPOSITONS BACKGROUND OF THE INVENTION

U.S. 4,675,358 discloses coating compositions employing phosphoric acid derivatives. Such compositions are not very hydrolytically stable. WO 96/08518 describ

water binders

10 disclose phosphi group.

that are compos

derivatives and their use in d compatibility with other g linkages. EP 391,230 of an alpha-aminomethylene containing at least one epoxy in water-borne compositions lestabilizes the coating llic coating compositions

comprising acrylic copolymers to reduce the gassing of aluminum flakes. Such compositions have limited hydrolytic stability and limited effectiveness.

# **SUMMARY OF THE INVENTION**

We have found that hydrophobic-substituted phosphonic acid derivatives
which are reaction products with hydroxy-functional copolymers are particularly
effective for inhibiting the corrosion of metallic pigments in water-borne
compositions. The invention concerns an aqueous coating composition comprising
a stabilized film-forming polymer, a metallic pigment and a compound which is the
reaction production of a, b and optionally c, wherein:

25 (a) is 5 to 95 weight percent of a phosphonic acid derivative consisting of one or both of

$$R + CH_2 + POH$$
 and  $R' = CH - POH$ 

wherein R and R' are selected from the group consisting of an aliphatic,
cycloaliphatic and aromatic substituent having 1 to 25 carbon atoms and optionally
up to 10 heteroatoms of at least one of oxygen, phosphorus and silicon;
(b) is 5 to 95 weight percent of a hydroxy-functional addition polymer with a
weight average molecular weight of 1000 to 30,000; and
(c) is 0 to 90 weight percent of a compound having one hydroxy-functional group.

15

20

30

35

Representative examples of phosphonic acid group-containing compounds are vinyl phosphonic acid, propyl and octyl phosphonic acid, and hydroxyethane diphosphonic acid.

Representative examples of hydroxy-functional polymers are addition

copolymers of methacrylates, vinylaromatics, acrylates,
acrylamides/methacrylamides and their derivatives, acrylonitrile, methacrylonitrile,
allylalcohol, maleates, itaconates and vinyl monomers. The copolymers are
hydroxy and/or acid functional. Typical comonomers useful to obtain the
hydroxy-functionality are 2-hydroxy ethyl acrylate, 2-hydroxyethyl methacrylate, 2hydroxy propyl acrylate, 2-hydroxy propyl methacrylate, allyl alcohol, 1,4
butenediol, 4-hydroxybutyl acrylate, bis-hydroxy ethyl maleate and the like.
Preferred hydroxy-functional copolymers are copolymers of styrene and allyl
alcohol. A preferred phosponic acid derivative is propyl and octyl phosphonic
acid.

The hydroxy functional copolymers are typically prepared in a freeradical initiated process using peroxy or azo initiators. The reaction between the hydroxy functional copolymer and the vinyl and/or alkyl phosphonic acid can be run in a fusion or solvent process where water is distilled.

The reaction products of the phosphonic acid derivatives and the hydroxy-functional copolymers are used to treat metallic pigments before the final blend is inverted in water. The final metallic pigment dispersions are stable from gassing.

#### **DETAILED DESCRIPTION**

25 Preferred coating compositions are the following:
where the reaction product as corrosion inhibitor is used in the form of a salt;

where the phosphonic acid derivative is propyl, octyl or vinylphosphonic acid;

where the hydroxy-functional product is based on a styrene-allyl copolymer;

where the corrosion inhibitor based on phosphonic acid has an acid value of 25 to 400 mgKOH/g;

where the composition is anionically or non-ionically stabilized, and where the film-forming polymers are anionically stabilized vinyl, acrylic and/or urethane emulsions.

Preferred phosphonic acid group-containing reaction products are those formed from one or more of vinyl phosphonic acid, propyl and octyl

WO 99/06450 PCT/US98/15761

phosphonic acid, and hydroxyethane diphosphonic acid with one or more hydroxy-functional copolymers of styrene and allyl alcohol. Preferably, R and R' have up to 12 carbon atoms and effect good hydrophobic-lipophilic balance (HLB).

5

#### **EXAMPLES**

#### Example 1

In a reaction vessel fitted with stirrer, thermometer, reflux condenser and Dean and Stark separator, a mixture of 300 parts xylene, 300 parts styrene/allyl alcohol copolymer with a molecular weight of 1600 was heated at 85-90°C till dissolved. There was then added 129.33 parts of octyl phosphonic acid (80% solution in water/ethanol=1/1). The temperature was raised to reflux (± 148°C) while water was removed. After 2 hours, 16 parts of water had been removed and the contents of the reactor were vacuum stripped. The reaction product was diluted with 270 parts of 2-butoxyethanol.

15

25

10

#### Test results:

	Solids	58.8%
	 Viscosity (Gardner Holdt)	W
	Acid value	148 mgKOH/g
20	Number Average MW	1700
	Weight Average MW	4400

#### Example 2

Procedure of Example 1 was repeated using 300 parts xylene, 300 parts styrene/allyl alcohol, 215.55 parts octyl phosphonic acid. In total, 28 parts of water were stripped in about 2 hours. After vacuum stripping, the reaction product was diluted in 310 parts of 2-butoxyethanol.

#### Test results:

	Solids	59.7%
30	Viscosity (Gardner Holdt)	V - 1/4
	Acid value	188 mgKOH/g
-	Number Average MW	1300
	Weight Average MW	3800

35

#### Example 3

Procedure of Example 1 was repeated in which 240 parts styrene/allyl alcohol copolymer were reacted with 73.8 parts of p-tert amylphenol and 137.33 parts of Cublen® K60 in 350 parts of xylene. Cublen® K60 is a 60% solution in

water of hydroxy ethane diphosphonic acid from Zschimmer and Schwarz Company.

Test results:

Solids

Viscosity

Acid value

Number Average MW

Weight Average MW

184 mgKOH/g

1560

4260

10

5

#### Example 4

Procedure of Example 1 was repeated in which 100 parts xylene, 300 parts of styrene/allyl alcohol copolymer and 85 parts of vinylphosphonic acid were used. Test results:

Solids 59.8%

Viscosity Z2

Acid value 178 mgKOH/g

Number Average MW 1100

Weight Average MW 2400

20

### Example 5

# Styrene/Allylic Alcohol Copolymer Modified with Propyl Phosphonic Acid

Into a 500 ml 3-neck round bottom flask fitted with a reflux condenser, water separator and air-driven stirrer, place the following and heat to 85°-90°C until dissolved:

25

30

**Xylene** 

50.0 grams

ARCO SAA100 resin

100.0 grams

Add the following and raise temperature to reflux (~148°C):

propyl phosphonic acid

36.2 grams

Continue to heat for 2 to 3 hours when approximately 5.6 grams of water will have been removed by azeotropic distillation. Cool to 100°C and begin vacuum strip to remove about 50 grams of solvent. At the end of the distillation, add the following to the reactor and allow to cool.

Butylcellosolve

90.0 grams

Fill out into a plastic container.

35

**Product** 

Acid Number

145

Weight Solids

59%

## Example 6

Paint Example:	Parts:
Dispersions	
Passivator Example 2	7.83
Butyl Glycol	58.42
Alu Flake (1)	30.75
Dimethylethanolamine	1.50
Thickener (2)	1.50
Aluminum Based Paint	
Dispersion of Passivator of Example 2	24.03
Latex (3)	27.53
D.I. water	47.55
Defoamer (4)	0.01
Thickener Combination (5)	0.88
Gassing Results (6)	
After 1 week	OK
After 2 weeks	OK
After 3 weeks	OK
After 4 weeks	OK .

- (1) Stapa Metallic R-607/Eckart
- (2) NOPCO DSX 1550/Henkel
- 5 (3) Latex Anionically Stabilized/DuPont
  - (4) Balab 3056A/Witco
  - (5) ASE-60/Polyphobe PP-107:78/22. Rohm & Haas/Union Carbide
  - (6) ALU Paint is mixed with iron oxide dispersion and kept in closed container at 49°C.

10

### Example 7

Paint Formula:	Parts:
Mineral spirits	4.9
(boiling range 140-160°C)	
Ethylene glycol-mono-n-hexylether	4.9
Ethylene glycol-mono-n-butylether	10.9
Aluminum Flake	17.8
(Silverline® SSP-353) (course	
aluminum flake 70% solids)	
Inhibitor of Example 2	4.3
Acrylic latex 30% in water	61.5
(Adjust till pH is 9) with	0.90
aminomethylpropanol	
The gassing was followed by measuring	5.3 ml
the ml of hydrogen (H <sub>2</sub> ) generated in 16	
hours at 60°C.	·

## WHAT IS CLAIMED IS:

- 1. An aqueous coating composition comprising a stabilized film-forming polymer, a metallic pigment and a compound which is the reaction product of (a), (b) and optionally (c), wherein:
- 5 (a) is 5 to 95 weight percent of a phosphonic acid derivative consisting of one or both of

$$R + CH_2 + OH$$
 and  $R' = CH - POH$ 

wherein R and R' are selected from the group consisting of an aliphatic,
cycloaliphatic and aromatic substituent having 1 to 25 carbon atoms and optionally
up to 10 heteroatoms of at least one of oxygen, phosphorus and silicon;
(b) is 5 to 95 weight percent of a hydroxy-functional addition polymer with a
weight average molecular weight of 1000 to 30,000; and

- (c) is 0 to 90 weight percent of a compound having one hydroxy-functional group.
- 15 2. A composition of Claim 1 where the reaction product is in the form of a salt.
  - 3. A composition of Claim 1 where the phosphonic acid derivative is propyl, octyl or vinylphosphonic acid.
- 4. A composition of Claim 1 where the hydroxy-functional product is based on a styrene-allyl alcohol copolymer.
  - 5. A composition of Claim 1 where the corrosion inhibitor based on phosphonic acid has an acid value of 25 to 400 mgKOH/g.
  - 6. A composition of Claim 1 where the film-forming polymers are selected from anionically stabilized vinyl, acrylic and urethane emulsions.
- 25 7. A composition of Claim 1 where the phosphonic acid group-containing reaction products are formed from one or more members selected from the groups consisting of vinyl phosphonic acid, propyl phosphonic acid, octyl phosphonic acid and hydroxyethane diphosphonic acid with one or more members selected from the group consisting of hydroxy-functional copolymers of styrene and allyl alcohol.
  - 8. A composition of Claim 7 comprising copolymers of styrene/allyl alcohol and propyl phosphonic acid.
    - 9. A composition of Claim 1 which is anionically stabilized.
    - 10. A composition of Claim 1 which is nonionically stabilized.

# INTERNATIONAL SEARCH RE. RT

Int tional Application No

			PCT/US 98/15761
IPC 6	SIFICATION OF SUBJECT MATTER C08F8/40 C09D5/38 C09C1	/64	
1	to International Patent Classification (IPC) or to both national class	ssification and IPC	
	S SEARCHED		
IPC 6	documentation searched (classification system followed by classifi CO9D CO8F CO9C	ication symbols)	
Document	ation searched other than minimum documentation to the extent the $oldsymbol{ iny}$	nat such documents are included	in the fields searched
Electronic	data base consulted during the international search (name of dat	a base and, where practical, see	rch terms used)
		·	
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the	relevant passages	Relevant to claim No.
<b>A</b>	EP 0 319 971 A (PPG INDUSTRIES 14 June 1989	1	
A	EP 0 401 833 A (NAT STARCH CHEM 12 December 1990	1	
A	US 5 637 441 A (BRENK MICHAEL 10 June 1997 see column 3, line 49 - column	1	
A	US 5 429 674 A (LAMERS PAUL H 4 July 1995 cited in the application	1	
Α .	EP 0 391 230 A (PPG INDUSTRIES 10 October 1990 cited in the application	1	
	er documents are listed in the continuation of box C.	X Patent family memb	ers are listed in annex.
A" documen	egories of cited documents : nt defining the general state of the an which is not	or priority gate and not i	after the international filing date
CONSIDE	red to be of particular relevance ocument but published on or after the international	invention  "X" document of particular re	evance: the claimed invention
citation	t which may throw doubts on priority claim(s) or cited to establish the publication date of another or other special reason (as specified)	involve an inventive step  "Y" document of particular re	ovel or cannot be considered to when the document is taken alone evenue.
P* documen	t published prior to the International filling data has	document is combined to	involve an inventive step when the with one or more other such docu- to being obvious to a person skilled
iater dia	n the priority date claimed	"&" document member of the	
	November 1998	Date of mailing of the inte	rnational search report
	iling address of the ISA	11/11/1998	
urd illd	European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Authorized officer Miller, A	

# INTERNATIONAL ARCH REPORT

Information on patent family members

In Itional Application No
PCT/US 98/15761

Patent document cited in search report	t	Publication date		Patent family member(s)	Publication date
EP 0319971	Α	14-06-1989	AU JP	2668188 A 1190765 A	06-07-1989 31-07-1989
EP 0401833	Α	12-12-1990	US CA DE. DE US	5023368 A 2017786 A,C 69003013 D 69003013 T 5126108 A	11-06-1991 08-12-1990 07-10-1993 20-01-1994 30-06-1992
US 5637441	Α	10-06-1997	DE BR DE EP ES JP	4423140 A 9503065 A 59501625 D 0689941 A 2113696 T 8058264 A	04-01-1996 11-06-1996 23-04-1998 03-01-1996 01-05-1998 05-03-1996
US 5429674		04-07-1995	AT AU CA CN DE EP ES JP WO	166072 T 3330795 A 2199170 A 1157622 A 69502506 D 0781298 A 2116759 T 9511778 T 9608518 A	15-05-1998 29-03-1996 21-03-1996 20-08-1997 18-06-1998 02-07-1997 16-07-1998 25-11-1997 21-03-1996
EP 0391230	A	10-10-1990	US AT AU CA CN DE DE ES JP JP JP JP	5034556 A 138952 T 617245 B 5213490 A 2012684 A,C 1046165 A 69027250 D 69027250 T 2090055 T 2577529 B 6340825 A 2290890 A 2568728 B 169220 B	23-07-1991 15-06-1996 21-11-1991 04-10-1990 03-10-1990 17-10-1990 11-07-1996 02-01-1997 16-10-1996 05-02-1997 13-12-1994 30-11-1990 08-01-1997 24-06-1993

INTERNATIONAL SEARCH RE RT

information on patent family members

In Itional Application No PCT/US 98/15761

Patent document cited in search report Publication date Patent family member(s) Publication date

EP 0391230 A US 5091451 A 25-02-1992

Form PCT/ISA/210 (patent family annex) (July 1992)